

METHOD FOR DESIGNING CLOCK WIRING CIRCUIT OF SEMICONDUCTOR INTEGRATED CIRCUIT

Patent Number: JP8044776
 Publication date: 1996-02-16
 Inventor(s): IIDA TAKASHI; others: 01
 Applicant(s): FUJITSU LTD
 Requested Patent:  JP8044776
 Application Number: JP19940178325 19940729
 Priority Number(s):
 IPC Classification: G06F17/50
 EC Classification:
 Equivalents:

Abstract

PURPOSE: To obtain improvement which suppresses clock skew as the time difference of a clock signal applied to a circuit element.

CONSTITUTION: As for the designing method for the clock wiring circuit of the semiconductor integrated circuit which designs logic, designs layout next, and arranges clock buffers 2 in a tree shape, a clock circuit at the time of the logic designing is not provided with the clock buffers 2, but provided with only an I/O input buffer 1, which is connected directly to a circuit element 3 which requires a clock signal; when the layout is designed, the clock buffers 2 determined by the number of circuit elements 3 requiring the clock signal are arranged in the tree shape as clock circuits, and a clock wiring branch pattern 5 is so arranged that the delay time of a clock wiring trunk pattern 4 approximates the delay time excluding the wiring delay time of a clock signal wire estimated from the overall area of the semiconductor integrated circuit.

Data supplied from the esp@cenet database - 12